SPEAKMAN® SEF-9000

Eyesaver® Service Sink Faucet with Eyewash/Drench Hose

EYEWASH FEATURES:

- Eyewash is connected to Speakman SC-5811-RCP service sink faucet's cold water integral stop port supply
- 6 ft. stainless steel supply hose
- Activated by squeeze valve with automatic stay open device
- (2) yellow plastic spray heads with flip top dust caps
- 3.06 gpm @ 30 psi performance (eyewash only)
- 2.66 gpm @ 30 psi (with sink on)
- Integral vacuum breaker and check valve

FAUCET FEATURES:

- ½ in. NPT female inlets supply
- Vandal resistant four-arm handles with color coded indexes
- Perfect® valves with ¼ turn ceramic cartridges
- 4 gpm (min) @ 20 psi
- Cast brass nozzle with ¾ in. hose thread, pail hook and top brace outlet
- Integral vacuum breaker

COMPLIANCE:

- ASME A112.18.1/CSA B125 certified (service sink faucet)
- ANSI/ISEA Z358.1 certified (eyewash)
- ASSE -1001 certified (service sink & faucet)

OPTIONS: Add suffix to model

- 4 in, wrist blade handles for service sink
- 5 ft. hose with hook for service sink
- Check valves in swivel assembly for service sink
- Addition of SE-370 thermostatic mixing valve for eyewash

WARRANTY:

• 3 year limited






□ -4WH

□ -5H□ -CK

□ -TW

W: WWW.SPEAKMAN.COM

NOTE: 1. Inlets are 1/2" NPT female. 2. All dimensions are in inches (millimeters) unless otherwise specified and are subject to change without DIMENSIONS: EyesaverTM service sink unit and the SC-5811-RCP service sink fitting can be purchased together as a SEF-9000 EyesaverTM service sink unit and the SC-5811-RCP service sink fitting can be purchased together as a SEF-9000 EyesaverTM service sink fitting.



556

R: JULY 2017