

SentinelPro™ Diverter Trim and Shower System (Valve not included)

MODELS:

- SLV-5060: 2.0 GPM (7.6 L/min) Flow Rate Shower Head
- SLV-5060-E15: 1.5 GPM (5.7 L/min) Flow Rate Shower Head

FEATURES:

- CPT-5001: Shower Valve Trim
- S-2272-E2: 2.0 GPM (7.6 L/min) Flow Rate Shower Head
- S-2272-E15: 1.5 GPM (5.7 L/min) Flow Rate Shower Head
- VS-100-PC: Hand Held Shower with Pause/Trickle Button
- VS-115: Supply Ell with Wall Flange
- VS-117: Vacuum Breaker
- VS-124: 42 in. Slide Bar
- CPT-1183: Transfer Valve Trim (Valve not included)
- VS-145: 69 in. Metal Stainless Steel Hose
- S-2500: Shower Arm with Wall Flange.

VALVE OPTIONS:

- CPV-TP2: Thermostatic/Pressure Balancing Valve Sweat & Thread Connections
- CPV-TV: Two-Way Diverter Valve for use with CPT-1183

STOCK FINISHES:



PC


STANDARDS:

- ASME A112.18.1/CSA B125.1 certified
- ADA Compliant

WARRANTY:


Visit www.speakman.com for full product warranty information

- See Speakman.com For Warranty Information



Information continues on next page

SentinelPro™ Diverter Trim and Shower System (Valve not included)



NOTES:

1. ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) UNLESS OTHERWISE SPECIFIED AND ARE SUBJECT TO CHANGE WITHOUT NOTICE.
2. THE LOCATIONS OF THE SLIDE BAR AND SUPPLY ELL ARE OPTIONAL, BUT RESTRICTED BY THE 69" HOSE LENGTH RUNNING FROM THE SUPPLY ELL CONNECTION TO THE HAND SHOWER AND THE 6" MINIMUM REQUIREMENT BETWEEN THE IN-LINE VACUUM BREAKER AND TOP OF THE HAND SHOWER (HAND SHOWER ADJUSTED TO HIGHEST POSITION).
3. FOR ADA MOUNTING LOCATIONS CONSULT ADAAG, ANSI A117.1, OR STATE REGULATIONS.