Sentinel Mark II[®] Pressure Balance ADA Shower Combination

FEATURES:

- Includes Sentinel Mark II® concealed anti-scald balanced pressure shower valve and handheld spray combination.
- Chrome plated brass wall plate with metal index.
- Chrome plated brass lever handle.
- Independent center sleeve allows up to 1 in. of rough-in variation.
- Adjustable temperature limit stop. Brass valve body.
- Pressure balancing & ceramic temperature regulating cartridge with built-in check valves.
- Four port valve with ½ in. NPT Male (1/2 in. copper sweat) inlets and outlets..
- S-1556 chrome plated tub spout diverter.
- In-line vacuum breaker.
- S-2500 shower arm and wall flange.
- VS-100-PC handshower with flow control device reduces flow to 2.5 gpm (9.46 L/min) maximum.
- Chrome 5' metal shower hose, ½ in. NPSF connectors.
- Swivel arm holder.
- 24 in. combination slide bar and grab bar, stainless steel and chrome.

OPTIONS:

• E175: 1.75 gpm (6.6 L/min) flow rate hand shower

STOCK FINISH:



STANDARDS:

- ASSE 1016 certified (shower valve)
- ASME 112.18.1/CSA B125.1 certified (shower valve)
- ADA Compliant

WARRANTY:

Visit www.speakman.com for full product warranty information


• See Speakman.com for warranty information



Information continues on next page

NOTE: 1. All dimensions are in inches (millimeters) unless otherwise specified and are subject to change without notice. 2. Unless otherwise specified, all inlets and outlets are 1/2" female copper sweat. 3. For ADA mounting locations, consult ADAAG, ANSI A117.1, or static regulations

Sentinel Mark II® Pressure Balance ADA Shower Combination



NOTE: 1. All dimensions are in inches (millimeters) unless otherwise specified and are subject to change without notice. 2. Unless otherwise specified, all inlets and outlets are 1/2" female copper sweat. 3. For ADA mounting locations, consult ADAAG, ANSI Al17.1, or static regulations

P: 800-537-2107

F: 800-977-2747

W: WWW.SPEAKMAN.COM R: 01-SEPTEMBER 2021