

SENSORFLO® FLUSH VALVE



SPEAKMAN®

SENSOR OPERATED FLUSH VALVES FOR URINALS & WATER CLOSETS

HARDWIRE & BATTERY POWERED

Durable, dependable and long-lasting: SENSORFLO Flush Valves from Speakman deliver commercial-grade performance you can count on. Built using Speakman's proven sensor technology, each water closet and urinal valve is designed for low maintenance from install to service life. Vandal-resistant features and rugged components keep high-traffic bathrooms clean, sanitary and usable. Available in configurations to meet a variety of application needs, including full battery operation or hardwired with battery backup.

FEATURES



ASSE 1037/ASME A112.1037/CSA B125.37 certified



ADA Compliant



WaterSense certified; models available:
SV-3005, SV-3105, SV-4012, SV-4128

TECHNICAL

- Commercial-grade, built-to-last chloramine-resistant components
- Hands-free automatic flush provides a cleaner, more sanitary environment
- Battery powered models for easy installation where power outlets are not accessible; Hardwire installation models provide flush after flush without replacing batteries
- Low battery indicator: Light flashes once per second when low, twice per second when critically low; Includes battery backup
- Uses 4 standard AA alkaline batteries (battery models-included); engineered to last 300,000 cycles; Battery back up uses 4 standard AAA alkaline batteries (wired models) which will last for 100,000 cycles for use during power outages
- Infrared sensor that detects movement 2 feet away and in a 15° vertical sweep
- Vandal-resistant: check-stop cap is secured with a set screw
- Operating pressure: 20 to 80 PSI (138 to 552 kPa)
- Operating temperature: 50 to 110 °F (10 to 43 °C)
- 3/4" (3000 Series); 1" (4000 Series) NPT check-stop, adjustable with flat-tipped screwdriver
- 3/4" top spud fixture connection (3000 Series); 1 1/2" top spud fixture connection (4000 Series)
- Manual override button located on side of unit

Urinal Flushometers



SV-3005
SV-3010



SV-3105
SV-3110

Water Closet Flushometers



SV-4012
SV-4016



SV-4116
SV-4128

SKU	DESCRIPTION	POWER	GPF
SV-3005	Exposed Sensor Battery Urinal Flushometer	Battery	0.50 GPF
SV-3010	Exposed Sensor Battery Urinal Flushometer	Battery	1.00 GPF
SV-3105	Exposed Wired Urinal Flushometer	Wired	0.50 GPF
SV-3110	Exposed Sensor Wired Urinal Flushometer	Wired	1.00 GPF
SV-4012	Exposed Sensor Battery Water Closet Flushometer	Battery	1.28 GPF
SV-4016	Exposed Sensor Battery Water Closet Flushometer	Battery	1.60 GPF
SV-4116	Exposed Sensor Wired Water Closet Flushometer	Wired	1.60 GPF
SV-4128	Exposed Sensor Wired Water Closet Flushometer	Wired	1.28 GPF

SPEAKMAN®

800-537-2107 | www.speakman.com

PPG Professional
PLUMBING GROUP

FLUSHOMETER 08/21 ©PPG 2021